

TECHNICAL DATA SHEET of BUTYL RECLAIM RUBBER

GRADE: De-BUTYL 80

CHEMICAL PROPERTIES

TECHNICAL DATA SPECIFICATION	TEST METHOD	BUTYL RECLAIM RUBBER
ACETONE EXTRACT (%)	ASTM D 297-18	9 ₊₃
ASH CONTENT (%)	ASTM D 297-18	5 ₊₃
CARBON BLACK (%)	ASTM E1131	32 ₊₄
VOLATILE MATTER (%)		1.0(Max)
RHC (%)	ASTM E1131	50(Min)

PHYSICAL PROPERTIES

SPECIFIC GRAVITY (gm/cc)	ASTM D 297-18	1.12 _{+0.02}
TENSILE STRENGTH(MPA)	ASTM D 412	7.5 (Min) MPA
ELONGATION (%)	ASTM D 412	480 Min
HARDNESS AT SHORE "A"	ASTM D 2240	51 ₊₅
MOONEY VISCOSITY(1+4@100°C)	ASTM D 1646	40-55

SNR Reclamations Pvt. Ltd.

114, Green Field, Near Pakhowal Road, Ludhiana - 141001 (Pb.) - INDIA.
Telephone: +91-161-4645114 **Mobile:** +91-9876066777, 750888368
Email : jas.snorreclamations@gmail.com, snorreclamations@gmail.com
Website : www.snorreclamations.com