

TECHNICAL DATA SHEET of EPDM RECLAIM RUBBER

GRADE: De-EPDM

CHEMICAL PROPERTIES

TECHNICAL DATA SPECIFICATION	TEST METHOD	De-EPDM
ACETONE EXTRACT (%)	ASTM D 297-18	30 ₊₅
ASH CONTENT (%)	ASTM D 297-18	14 ₊₂
CARBON BLACK (%)	ASTM E1131	25 ₊₂
VOLATILE MATTER (%)		1.0(Max)
RHC (%)	ASTM E1131	30(Min)

PHYSICAL PROPERTIES

SPECIFIC GRAVITY (gm/cc)	ASTM D 297-18	1.14 _{+0.02}
TENSILE STRENGTH(Kg/cm ²)	ASTM D 412	60(Min)
ELONGATION (%)	ASTM D 412	375 Min
HARDNESS AT SHORE "A"	ASTM D 2240	55 ₊₅
MOONEY VISCOSITY(1+4@100°C)	ASTM D 1646	40-60

SNR Reclamations Pvt. Ltd.

114, Green Field, Near Pakhowal Road, Ludhiana - 141001 (Pb.) - INDIA.

Telephone: +91-161-4645114 Mobile: +91-9876066777, 750888368

Email : jas.snorreclamations@gmail.com, snorreclamations@gmail.com

Website : www.snorreclamations.com